

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : DRY FLEX® SF Component A

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
 Use of the substance/mixture : Durable fine surface filler
 Product only to be used in combination with component B.

1.2.2. Uses advised against

No additional information available.

1.3. Details of the supplier of the safety data sheet

Repair Care International
 Cartografenweg 34
 5141 MT Waalwijk - Nederland
 T + 31(0) 416 650095 - F + 31(0) 416 652024
info@repair-care.com - www.repair-care.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Remark
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0344 892 0111	Only for the purpose of informing medical personnel in cases of acute intoxications

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] with its amendment Regulation (EU) 2016/1179

Skin corrosion/irritation, Category 2 H315
 Serious eye damage/eye irritation, Category 2 H319
 Skin sensitisation, Category 1 H317
 Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
 Full text of H statements : see section 16


Adverse physicochemical, human health and environmental effects

Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] with its amendment Regulation (EU) 2016/1179

Hazard pictograms (CLP) :



Signal word (CLP) :

Warning

Hazardous ingredients :

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol; reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)

Hazard statements (CLP) :

H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H319 - Causes serious eye irritation.
 H411 - Toxic to aquatic life with long lasting effects.



Precautionary statements (CLP) :

P261 - Avoid breathing Vapours.
 P264 - Wash hands and forearms thoroughly after handling.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P273 - Avoid release to the environment.

DRY FLEX® SF Component A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

EUH-statements	: P280 - Wear eye protection, protective clothing, protective gloves. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. : EUH205 - Contains epoxy constituents. May produce an allergic reaction.
Hazard pictograms (CLP)	:   GHS07 GHS09
Signal word (CLP)	: Warning
Hazardous ingredients	: oxirane, mono[(C12-14-alkyloxy)methyl] derivs.; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol; reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)
Hazard statements (CLP)	: H317 - May cause an allergic skin reaction.
Precautionary statements (CLP)	: P261 - Avoid breathing Vapours. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear eye protection, protective clothing, protective gloves. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
EUH-statements	: EUH205 - Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP] with its amendment Regulation (EU) 2016/1179
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	< 50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	(CAS-No.) 9003-36-5 (EC-No.) 500-006-8 (REACH-no) 01-2119454392-40	< 25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Talc substance with national workplace exposure limit(s) (GB)	(CAS-No.) 14807-96-6 (EC-No.) 238-877-9 (REACH-no) 01-2120140278-58	< 20	Not classified
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	(CAS-No.) 68609-97-2 (EC-No.) 271-846-8 (EC Index-No.) 603-103-00-4 (REACH-no) 01-2119485289-22	< 15	Skin Irrit. 2, H315 Skin Sens. 1, H317

Specific concentration limits:

Name	Product identifier	Specific concentration limits
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	(C ≥ 5) Skin Irrit. 2, H315 (C ≥ 5) Eye Irrit. 2, H319

Comments : Without VOC (volatile organic compounds)

Full text of H-phrases: see section 16

DRY FLEX® SF Component A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Take off contaminated clothing. Wash with plenty of water/.... If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting without medical advice. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Presents no particular fire or explosion hazard.
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO ₂).

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it. Scoop absorbed substance into closing containers. Store away from other materials.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Provide good ventilation in process area to prevent formation of vapour. Avoid all eye and skin contact and do not breathe vapour and mist.
Handling temperature	: 5 - 50 °C
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep only in the original container in a cool, well-ventilated place.
Incompatible products	: Strong bases. Strong acids. Oxidation agents.

DRY FLEX® SF Component A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Storage temperature : 10 - 30 °C
Heat and ignition sources : Keep away from heat and direct sunlight.

7.3. Specific end use(s)

Industrial. Professional.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Talc (14807-96-6)		
United Kingdom	Local name	Talc
United Kingdom	WEL TWA (mg/m ³)	1 mg/m ³ respirable dust
United Kingdom	Regulatory reference	EH40. HSE

8.2. Exposure controls

Personal protective equipment:

Protective clothing. Gloves. Protective goggles.

Hand protection:

Wear suitable gloves resistant to chemical penetration. Chemical resistant gloves (according to European standard NF EN 374 or equivalent).

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	nitrile rubber (NBR), butyl rubber, Polyvinylchloride (PVC)	6 (> 480 minutes)	0.11		EN 374

Eye protection:

Use splash goggles when eye contact due to splashing is possible

Type	Use	Characterizations	Standard
Protective goggles	Droplet		EN 166

Skin and body protection:

Wear suitable protective clothing. CEN : EN 340; EN 369; EN 465

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. EN 143



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Paste.
Colour : Beige.
Odour : characteristic.
Odour threshold : No data available.
pH : No data available.
Relative evaporation rate (butylacetate=1) : No data available.
Melting point : < 0 °C
Freezing point : No data available.
Boiling point : > 200 °C
Flash point : > 93 °C
Auto-ignition temperature : No data available.

DRY FLEX® SF Component A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Decomposition temperature	: No data available.
Flammability (solid, gas)	: No data available.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: 1
Relative density	: 1,44
Solubility	: Poorly soluble in water.
Log Pow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

9.2. Other information

No additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidation agent.

10.6. Hazardous decomposition products

Combustion generates: Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

LD50 dermal rat	26800 mg/kg
-----------------	-------------

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)

LD50 oral rat	> 10000 mg/kg
LD50 dermal rat	> 2000 mg/kg

reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

LD50 oral rat	15000 mg/kg
LD50 dermal rabbit	23000 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

NOAEL (chronic, oral, animal/male, 2 years)	100 mg/kg bodyweight
---------------------------------------------	----------------------

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)

NOAEL (chronic, oral, animal/male, 2 years)	250 mg/kg bodyweight
---------------------------------------------	----------------------

Reproductive toxicity	: Not classified
-----------------------	------------------

STOT-single exposure	: Not classified
----------------------	------------------

DRY FLEX® SF Component A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

LC50 other aquatic organisms 1 96hr > 5000 mg/l leuciscus idus (OECD 203)

EC50 Daphnia 1 48hr 6,07 mg/l OECD 202

ErC50 (algae) 72hr 843,75 mg/l OECD 201

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)

LC50 other aquatic organisms 1 96hr 2,54 mg/l leuciscus idus

EC50 Daphnia 1 2,55 mg/l

ErC50 (algae) 48hr 1,8 mg/l

reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

LC50 other aquatic organisms 2 96hr 2 mg/l leuciscus idus

EC50 Daphnia 1 48hr 1,8 mg/l

ErC50 (algae) 72hr 11 mg/l

12.2. Persistence and degradability

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

Persistence and degradability Readily biodegradable.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)

Persistence and degradability not readily degradable in water.

12.3. Bioaccumulative potential

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

Log Pow 3,77 OECD 107

Bioaccumulative potential not bioaccumulative.

12.4. Mobility in soil

No additional information available.

12.5. Results of PBT and vPvB assessment

DRY FLEX® SF Component A

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Empty containers should be taken for recycle, recovery or waste in accordance with local regulation.

Ecology - waste materials : Avoid release to the environment.

European List of Waste (LoW) code : 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information






In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
3082	3082	3082	3082	3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

DRY FLEX® SF Component A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

ADR	IMDG	IATA	ADN	RID
N.O.S. (CONTAINS ; reaction product: bisphenol-A- (epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenol)	N.O.S. (CONTAINS ;reaction product: bisphenol-A- (epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenol)	N.O.S. (CONTAINS ;reaction product: bisphenol-A- (epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenol)	N.O.S. (CONTAINS ;reaction product: bisphenol-A- (epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenol)	N.O.S. (CONTAINS ;reaction product: bisphenol-A- (epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenol)
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS ; reaction product: bisphenol-A- (epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenol), 9, III, (E)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS ;reaction product: bisphenol-A- (epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenol), 9, III, MARINE POLLUTANT	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS ;reaction product: bisphenol-A- (epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenol), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS ;reaction product: bisphenol-A- (epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenol), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS ;reaction product: bisphenol-A- (epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenol), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes

No supplementary information available.

14.6. Special precautions for user


- Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 601, 375
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90

DRY FLEX® SF Component A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Orange plates : 

Tunnel restriction code (ADR) : E

- Transport by sea

Special provisions (IMDG) : 274, 335, 969
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP2, TP29
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A
MFAG-No : 171

- Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L
Special provisions (IATA) : A97, A158, A197
ERG code (IATA) : 9L

- Inland waterway transport

Classification code (ADN) : M6
Special provisions (ADN) : 274, 335, 375, 601
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP
Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : M6
Special provisions (RID) : 274, 335, 375, 601
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBV
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31
Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

DRY FLEX® SF Component A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Directive 2012/18/EU (SEVESO III) : E2 Hazardous to the Aquatic Environment in Category Chronic 2

15.1.2. National regulations

No additional information available.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Revised safety data sheet in accordance with commission regulation (EU) No 2016/1179.

Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	

Abbreviations and acronyms:

SDS	Safety Data Sheet
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PBT	Persistent Bioaccumulative Toxic
vPvB	Very Persistent and Very Bioaccumulative
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
LC50	Median lethal concentration
LD50	Median lethal dose
CAS	CAS (Chemical Abstracts Service) number
EG-nr	EINECS- en ELINCS-number
EINECS	European Inventory of Existing Commercial Substances
OEL	Occupational Exposure Limit

Data sources : according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179.

Other information : REACH Disclaimer:
This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number). **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H315	Causes skin irritation.

DRY FLEX® SF Component A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product